



QINGDAO KETER TYRE CO., LTD

ADD: ROOM1401, BUILDING NO.2, SHENGHE MANSION, NO.58
SHANDONGTOU ROAD, QINGDAO, CHINA 266100
Tel: 86-532-55579147, 86-532-55579148
Fax: 86-532-55579145 E-mail: info@keter tyre.com



INTERTRAC

PCR



NANO ARMOUR
Excellent wear resistance by Nano-composite



EARTH CARE
Low fuel consumption by Nano-composite
Low rolling resistance



Nano Armour, excellent wear resistance on tread by Nano-composite.
Human Protection, instantaneous elc-conduction performance by compound.
Earth Care, low fuel consumption by low rolling resistance.

INTERTRAC, a higher level brand with leading technology from Keter Company.

Nano carbon black is applied in **INTERTRAC** tyres, it is the core and the soul of the tyres, which dramatically improves the tyres in a safe, durable and environmental-friendly way. Nowadays green and safe tyres are highly needed by the world."





FOUR LONGITUDINAL GROOVES

- Effective drainage and wet grip performance
- Better wet safety

WIDE PATTERN GROOVE DESIGN

- Avoid air flow vibration frequency effectively, reduce the abnormal wear and extend the life of the tyre



RUN-FLAT DESIGN

- Better handling performance
- Ensure the safety when the air's leaking



TC555 PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
225/50ZRF17	98W	7J	658/26.0	233/ 9.0	7.9/10.0	320AA
225/55ZRF17	101/XLW	7J	680/26.8	233/ 9.2	7.9/10.0	320AA
255/40ZRF18	99/XLW	9J	661/26.0	260/10.2	7.9/10.0	320AA
225/45ZRF18	95W	7½J	659/26.0	225/ 9.0	7.9/10.0	320AA
245/45ZRF18	100W	8J	677/27.0	243/10.0	7.9/10.0	320AA
245/50ZRF18	100W	7½J	703/28.0	253/10.0	7.9/10.0	320AA
255/55ZRF18	109V	8J	737/29.0	265/10.0	7.9/10.0	320AA
255/50ZRF19	107/XLW	8J	739/29.1	265/10.4	7.9/10.0	320AA




BLOCK TREAD DESIGN

- The block tread design provides outstanding off-road traction and gripping power.

3 MAIN ZIGZAG GROOVES

- 3 main zigzag grooves provide excellent traction performance.



BALANCED VOID RATIO

- The balanced void ratio efficiently removes mud and dirt to provide continuous off-road traction.

TCMT PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)
35*12.5R17LT	121Q	10J	883 / 34.8	318 / 12.5
33*12.5R18LT	118Q	10J	832 / 32.8	318 / 12.5
35*12.5R18LT	123Q	10J	883 / 34.8	318 / 12.5
LT235/75R15	116/113Q	6½J	739 / 29.1	235 / 9.3
30X9.50R15LT	104Q	7½J	756 / 29.8	240 / 9.4
31X10.50R15LT	109Q	8½J	781 / 30.7	268 / 10.6
LT245/75R16	120/116Q	7½J	780 / 30.7	248 / 9.8
LT265/75R16	123/120Q	7½J	810 / 31.9	267 / 10.5
LT285/75R16	126/123Q	8J	840 / 33.1	296 / 11.3
LT265/70R17	121/118Q	8J	810 / 31.9	272 / 10.7
LT285/70R17	121/118Q	8½J	838 / 33.0	292 / 11.5
33X12.50R20LT	114Q	10J	883 / 34.8	318 / 12.5
35X12.50R20LT	121Q	10J	838 / 33.0	318 / 12.5

TC515

PCR



'BEVEL EDGE' DESIGN FOR GROOVES

- Avoiding irregular wear
- Longer tire life



'EU TIRE LABELING REGULATION' APPROVED

- Low energy consumption
- Good wetland performance
- Low noise

TC515 PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)	UTQG
175/60R13	77H	5J	540/21.3	177/7.0	7.5/9.4	380AA
155/70R13	73T	4½J	548/21.6	157/6.2	7.5/9.4	380AA
165/70R13	79T	5J	562/22.1	170/6.7	7.5/9.4	380AA
165/70R13	79H	5J	562/22.1	170/6.7	7.5/9.4	380AA
175/70R13	82T	5J	576/22.7	177/7.0	7.5/9.4	380AA
175/70R13	82H	5J	576/22.7	177/7.0	7.5/9.4	380AA
185/70R13	86H	5½J	590/23.2	189/7.4	7.5/9.4	380AA
155/80R13	79T	4½J	578/22.8	157/6.2	7.5/9.4	380AA
165/80R13	83H	4½J	594/23.4	170/6.7	7.5/9.4	380AA
185/60R14	82H	5½J	578/22.8	189/7.4	7.5/9.4	380AA
195/60R14	86H	6J	590/23.2	201/7.9	7.7/9.7	380AA
205/60R14	88H	6J	602/23.7	209/8.2	7.7/9.7	380AA
155/65R14	75H	4½J	558/22.0	157/6.2	7.7/9.7	380AA
165/65R14	79H	5J	570/22.4	170/6.7	7.5/9.4	380AA
175/65R14	82T	5J	584/23.0	177/7.0	7.5/9.4	380AA
175/65R14	82H	5J	584/23.0	177/7.0	7.5/9.4	380AA
175/65R14	86T	5J	584/23.0	177/7.0	7.5/9.4	380AA
175/65R14	86H	5J	584/23.0	177/7.0	7.5/9.4	380AA
185/65R14	86T	5½J	596/23.5	189/7.4	7.5/9.4	380AA
185/65R14	86H	5½J	596/23.5	189/7.4	7.5/9.4	380AA
195/65R14	89H	6J	610/24.0	201/7.9	7.7/9.7	380AA
185/70R14	88T	5½J	616/24.3	189/7.4	7.5/9.4	380AA
185/70R14	88H	5½J	616/24.3	189/7.4	7.5/9.4	380AA
195/70R14	91T	6J	630/24.8	201/7.9	7.7/9.7	380AA
195/70R14	91H	6J	630/24.8	201/7.9	7.7/9.7	380AA
195/70R14	95H	6J	630/24.8	201/7.9	7.7/9.7	380AA
205/70R14	98T	6J	644/25.4	209/8.2	7.9/10.0	380AA
195/75R14	92H	5½J	648/25.5	196/7.7	7.7/9.7	380AA
195/60R15	82V	6J	577/22.7	201/7.9	7.7/9.7	380AA
175/55R15	77H	5½J	573/22.6	182/7.2	7.7/9.7	380AA
185/55R15	82V	6J	585/23.0	188/7.4	7.5/9.4	380AA
195/55R15	85V	6J	595/23.4	201/7.9	7.7/9.7	380AA
175/60R15	81H	5J	591/23.3	177/7.0	7.5/9.4	380AA
185/60R15	84H	5½J	603/23.7	189/7.4	7.5/9.4	380AA
185/60R15	88H	5½J	603/23.7	189/7.4	7.5/9.4	380AA
195/60R15	88H	6J	615/24.2	201/7.9	7.7/9.7	380AA

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)	UTQG
195/60R15	88V	6J	615/24.2	201/7.9	7.7/9.7	380AA
205/60R15	91H	6J	627/24.7	209/8.2	7.7/9.7	380AA
205/60R15	91V	6J	627/24.7	209/8.2	7.7/9.7	380AA
225/60R15	96H	6½J	651/25.6	228/9.0	7.7/9.7	380AA
165/65R15	81H	5J	595/23.4	170/6.7	7.7/9.7	380AA
175/65R15	84H	5J	609/24.0	177/7.0	7.7/9.7	380AA
185/65R15	88T	5½J	621/24.4	189/7.4	7.5/9.4	380AA
185/65R15	88H	5½J	621/24.4	189/7.4	7.5/9.4	380AA
195/65R15	91H	6J	635/25.0	201/7.9	7.7/9.7	380AA
195/65R15	91V	6J	635/25.0	201/7.9	7.7/9.7	380AA
205/65R15	94H	6J	647/25.5	209/8.2	7.7/9.7	380AA
205/65R15	94V	6J	647/25.5	209/8.2	7.7/9.7	380AA
215/65R15	100H	6½J	661/26.0	221/8.7	7.7/9.7	380AA
195/70R15	97/XLS	6J	655/25.8	201/7.9	7.7/9.7	380AA
205/70R15	96H	6J	609/24.0	209/8.2	7.9/10.0	380AA
215/70R15	98T	6J	683/26.9	221/8.7	7.9/10.0	380AA
225/70R15	100T	6½J	697/27.4	228/9.0	7.9/10.0	380AA
225/70R15	100H	6½J	697/27.4	228/9.0	7.9/10.0	380AA
195/50R16	84H	6J	602/23.7	201/7.9	7.7/9.7	380AA
205/50ZR16	87W	6½J	612/24.1	201/7.9	7.7/9.7	380AA
225/50ZR16	92W	7J	632/24.9	214/8.4	7.7/9.7	380AA
225/50ZR16	96W	7J	632/24.9	233/9.2	7.7/9.7	380AA
185/55R16	83V	6J	610/24.0	233/9.2	7.7/9.7	380AA
195/55R16	87H	6J	620/24.4	194/7.6	7.7/9.7	380AA
195/55R16	87V	6J	620/24.4	201/7.9	7.7/9.7	380AA
205/55R16	91V	6½J	632/24.9	201/7.9	7.7/9.7	380AA
205/55ZR16	91W	6½J	632/24.9	214/8.4	7.7/9.7	380AA
205/55ZR16	94W	6½J	632/24.9	214/8.4	7.7/9.7	380AA
215/55ZR16	97W	7J	642/25.3	214/8.4	7.7/9.7	380AA
225/55ZR16	99W	7J	654/25.7	226/8.9	7.7/9.7	380AA
205/60R16	92H	6J	652/25.7	209/8.2	7.7/9.7	380AA
205/60R16	92V	6J	652/25.7	209/8.2	7.7/9.7	380AA
215/60R16	95H	6½J	664/26.1	221/8.7	7.7/9.7	380AA
215/60R16	95V	6½J	664/26.1	221/8.7	7.7/9.7	380AA
225/60R16	98H	6½J	676/26.6	228/9.0	7.9/10.0	380AA
225/60R16	102H	6½J	676/26.6	228/9.0	7.9/10.0	380AA
205/65R16	95V	6J	672/26.5	209/8.2	7.7/9.7	380AA
215/65R16	98H	6½J	686/27.0	221/8.7	7.7/9.7	380AA

TC525

PCR



GRIP FORMULA

- Nano carbon black inside
- Excellent wet grip performance

'HULK' DESIGN FOR SHOULDER

- Avoiding irregular wear
- Longer tire life



TC525 PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)	UTQG
235/50ZR17	100/XLW	7½J	668/26.3	245/9.6	7.7/9.7	320AA
205/65ZR17	95/XLW	6½J	658/25.9	214/8.4	7.7/9.7	320AA
215/65ZR17	98W	7J	668/26.3	226/8.9	7.7/9.7	320AA
225/65ZR17	101W	7J	680/26.8	233/9.2	7.7/9.7	320AA
235/65ZR17	103W	7½J	690/27.2	245/9.6	7.7/9.7	320AA
225/60R17	99V	6½J	702/27.6	228/9.0	7.7/9.7	320AA
235/60R17	102V	7J	714/28.1	240/9.4	7.7/9.7	320AA
215/35ZR18	84W	7½J	607/23.9	218/8.6	7.7/9.7	320AA
255/35ZR18	94/XLY	9J	635/25.0	260/10.2	7.7/9.7	320AA
265/35R18	97Y	9½J	643/25.3	230/9.1	7.7/9.7	320AA
225/40ZR18	92W	8J	637/25.1	230/9.1	7.7/9.7	320AA
235/40ZR18	95W	8½J	645/25.4	241/9.5	7.7/9.7	320AA
245/40ZR18	97W	8½J	653/25.7	248/9.8	7.7/9.7	320AA
255/40ZR18	99/XLW	9J	661/26.0	260/10.2	7.7/9.7	320AA
225/45ZR18	95W	7½J	659/25.9	225/8.9	7.7/9.7	320AA
235/45ZR18	98W	8½J	669/26.3	236/9.3	7.7/9.7	320AA
245/45ZR18	100W	8J	677/26.7	243/9.6	7.7/9.7	320AA
255/45ZR18	103W	8½J	687/27.0	255/10.0	7.7/9.7	320AA
235/50ZR18	101W	7½J	693/27.3	245/9.6	7.7/9.7	320AA
245/50ZR18	100W	7½J	703/27.7	253/10.0	7.7/9.7	320AA
225/65ZR18	102/XLW	7J	705/27.8	233/9.2	7.7/9.7	320AA
235/55R18	104W	7½J	715/28.1	245/9.6	7.7/9.7	320AA
235/55R18	100T	7½J	715/28.1	245/9.6	7.7/9.7	320AA
225/60R18	104HV	6½J	727/28.6	228/9.0	7.7/9.7	320AA
225/35ZR19	88W	8J	641/25.2	230/9.1	7.7/9.7	320AA
235/35ZR19	91W	8½J	647/25.5	241/9.5	7.7/9.7	320AA
245/35ZR19	93W	8½J	655/25.8	248/9.8	7.7/9.7	320AA
255/35ZR19	96/XLW	9J	661/26.0	260/10.2	7.7/9.7	320AA
245/40ZR19	98/XLW	8½J	679/26.7	248/9.8	7.7/9.7	320AA
255/40ZR19	100/XLW	9J	687/27.0	260/10.2	7.7/9.7	320AA
235/45ZR19	99/XLW	8J	695/27.4	236/9.3	7.7/9.7	320AA
245/45ZR19	102W	8J	703/27.7	243/9.6	7.7/9.7	320AA
225/35ZR20	90W	8J	666/26.2	230/9.1	7.7/9.7	320AA
235/35ZR20	92W	8½J	672/26.5	241/9.5	7.7/9.7	320AA
245/35ZR20	95Y	8½J	680/26.8	248/9.8	7.7/9.7	320AA
255/35ZR20	97/XLW	9J	686/27.0	260/10.2	7.7/9.7	320AA
275/40ZR20	106W	9½J	728/28.7	278/10.9	7.7/9.7	320AA
265/45ZR20	108W	9J	746/29.4	266/10.5	7.7/9.7	320AA
265/50R20	111V	8½J	774/30.5	277/10.9	7.7/9.7	320AA

'LEFT ≠ RIGHT' PATTERN DESIGN

- Balance draining with traction
- Good handling. More security



'SALIX LEAF' BLOCK DESIGN

- Avoiding irregular wear



SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)	UTQG
235/60R15	98V	7J	663/26.1	240/9.4	7.7/9.7	320AA
245/60R15	101V	7J	675/26.6	248/9.8	7.7/9.7	320AA
215/40ZR16	86W	7½J	578/22.8	218/8.6	7.7/9.7	320AA
195/45R16	84V	6½J	582/22.9	195/7.7	7.7/9.7	380AA
205/45ZR16	87W	7J	590/23.2	206/8.1	7.7/9.7	320AA
225/55ZR16	99W	7J	654/25.7	228/9.0	7.7/9.7	320AA
225/65R16	100V	6½J	698/27.5	228/9.0	7.7/9.7	320AA
205/40ZR17	84W	7½J	596/23.5	212/8.3	7.7/9.7	320AA
215/40ZR17	87W	7½J	604/23.8	213/8.4	7.7/9.7	320AA
245/40ZR17	95/XLW	8½J	628/24.7	248/9.8	7.7/9.7	320AA
205/45ZR17	88W	7J	616/24.3	206/8.1	7.7/9.7	320AA
215/45ZR17	91W	7J	626/24.6	213/8.4	7.7/9.7	320AA
225/45ZR17	94W	7½J	634/25.0	225/8.9	7.7/9.7	320AA
235/45ZR17	97W	8J	644/25.4	236/9.3	7.7/9.7	320AA
245/45ZR17	99W	8J	652/25.7	243/9.6	7.7/9.7	320AA
205/50ZR17	93W	6½J	638/25.1	214/8.4	7.7/9.7	320AA

TC565

PCR



TC565 PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
215/75R15	100T	6J	703/27.7	216/8.5	8.7/11.0	440AA
225/75R15	102T	6J	719/28.3	223/8.8	8.7/11.0	440AA
235/75R15	105S	6½J	733/28.9	235/9.3	8.7/11.0	440AA
235/60R16	100V	7J	688/27.1	240/9.4	8.2/10.3	440AA
235/65R16	103H	7J	712/28.0	240/9.4	8.2/10.3	440AA
255/65R16	109H	7½J	738/29.1	260/10.2	8.5/10.7	440AA
215/70R16	100T	6½J	708/27.9	221/8.7	8.7/11.0	440AA
225/70R16	103T	6½J	722/28.4	228/9.0	8.5/10.7	440AA
235/70R16	106T	7J	736/29.0	240/9.4	8.7/11.0	440AA
245/70R16	107T	7J	750/29.5	248/9.8	8.7/11.0	440AA
255/70R16	111T	7½J	764/30.1	260/10.2	8.7/11.0	440AA
265/70R16	112T	8J	778/30.6	272/10.7	8.7/11.0	440AA
275/70R16	114H	8J	792/31.2	279/11.0	8.7/11.0	440AA
235/55R17	103V	7½J	690/27.2	245/9.6	8.5/10.7	440AA
215/60R17	96H	6½J	690/27.2	221/8.7	8.2/10.3	440AA
225/60R17	99H	6½J	712/28.0	221/8.7	8.2/10.3	440AA
255/60R17	106V	7½J	738/29.1	260/10.2	8.7/11.0	440AA
225/65R17	106H	6½J	724/28.5	223/8.8	8.5/10.7	440AA
235/65R17	108H	7J	738/29.1	240/9.4	8.5/10.7	440AA
245/65R17	111H	7J	750/29.5	248/9.8	8.5/10.7	440AA
255/65R17	110H	7½J	764/30.1	260/10.2	8.5/10.7	440AA
265/65R17	116H	8J	776/30.6	272/10.7	8.7/11.0	440AA
275/65R17	115H	8J	790/31.1	279/11.0	8.5/10.7	440AA
285/65R17	116H	8½J	802/31.6	292/11.5	8.5/10.7	440AA
265/70R17	115T	8J	804/31.7	272/10.7	8.7/11.0	440AA
235/55R18	104V	7½J	715/28.1	245/9.6	8.5/10.7	440AA
255/55R18	109V	8J	737/29.0	265/10.4	8.7/11.0	440AA
235/60R18	107H	7J	739/29.1	240/9.4	8.8/11.1	440AA
265/60R18	110H	8J	775/30.5	272/10.7	8.2/10.3	440AA
275/65R18	116H	8J	815/32.1	279/11.0	8.5/10.7	440AA
285/50R20	116V	9J	794/31.3	292/11.5	8.2/10.3	440AA

BLOCK TO BLOCK DESIGN

- Good grip performance
- Better handling & controllability



'DE-NOISE' SHOULDER DESIGN

- Lower noise during running
- Driving comfortably



TC585

PCR



'HEAT-RELEASE' DESIGN

- Longer tire life

'STRAIGHT FORWARD' DESIGN

- Great straight-line driving stability
- More safety



'RAINY RIDER' DESIGN

- Effective drainage and wet grip performance
- Better wet safety



TC585 PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
31x10.50R15LT	109S	8½J	775/30.5	268/10.6	11.6/14.6	—
LT215/75R15	100/97R	6J	703/27.7	216/8.5	11.6/14.6	—
LT225/75R15	108/104R	6J	719/28.3	223/8.8	11.6/14.6	—
LT235/75R15	116/113R	6½J	733/28.9	237/9.3	11.6/14.6	—
LT235/75R15	116/113Q	6½J	733/28.9	237/9.3	11.6/14.6	—
LT265/70R16	121/118S	8J	778/30.6	267/10.5	11.6/14.6	—
LT265/70R16	121/118R	8J	778/30.6	267/10.5	11.6/14.6	—
LT225/75R16	115/112Q	6J	744/29.3	223/8.8	11.6/14.6	—
LT225/75R16	115/112R	6J	744/29.3	223/8.8	11.6/14.6	—
LT245/75R16	120/116Q	7J	774/30.5	248/9.8	11.6/14.6	—
LT245/75R16	120/116R	7J	774/30.5	248/9.8	11.6/14.6	—
LT265/75R16	123/120Q	7½J	804/31.7	267/10.5	11.6/14.6	—
LT265/75R16	123/120R	7½J	804/31.7	267/10.5	11.6/14.6	—
LT285/75R16	126/123R	8J	834/32.8	289/11.4	11.6/14.6	—
LT215/85R16	115/112R	6J	778/30.6	216/8.5	11.6/14.6	—
LT215/85R16	110/107Q	6J	778/30.6	216/8.5	11.6/14.6	—
LT235/85R16	120/116Q	6½J	806/31.7	235/9.3	11.6/14.6	—
LT235/85R16	120/116R	6½J	806/31.7	235/9.3	11.6/14.6	—
LT245/70R17	119/116R	7J	776/30.6	248/9.8	11.6/14.6	—
LT245/70R17	119/116S	7J	776/30.6	248/9.8	11.6/14.6	—
LT265/70R17	121/118R	8J	810/31.9	267/10.5	11.6/14.6	—
LT265/70R17	121/118S	8J	810/31.9	267/10.5	11.6/14.6	—
LT285/70R17	121/118R	8J	838/33.0	289/11.4	11.6/14.6	—
LT245/75R17	121/118R	7J	806/31.7	248/9.8	11.6/14.6	—
LT235/80R17	120/117Q	6½J	808/31.8	237/9.3	11.6/14.6	—
LT235/80R17	120/117R	6½J	808/31.8	237/9.3	11.6/14.6	—
LT265/70R18	124/121S	8J	835/32.9	267/10.5	11.6/14.6	—
LT275/65R18	123/120S	8J	815/32.1	279/11.0	11.6/14.6	—
LT30x9.50R15	104Q	7½J	750/29.5	240/9.4	11.6/14.6	—

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
215R15C	113/111S	6	724/28.5	218/8.6	9.6/12.1	—
205R16C	110/108S	6	736/29.0	208/8.2	9.6/12.1	—
215/70R16	100T	6½J	708/27.9	221/8.7	9.6/12.1	480AB
235/70R16	106S	7J	736/29.0	240/9.4	9.6/12.1	480AB
235/70R16	106T	7J	736/29.0	240/9.4	9.6/12.1	480AB
245/70R16	107S	7J	750/29.5	248/9.8	9.6/12.1	480AB
245/70R16	107T	7J	750/29.5	248/9.8	9.6/12.1	480AB
255/70R16	111T	7½J	764/30.1	260/10.2	9.6/12.1	480AB
265/70R16	112S	8	778/30.6	272/10.7	9.6/12.1	480AB
275/70R16	114T	8	792/31.2	279/11.0	9.6/12.1	—
265/70R17	115S	8J	804/31.7	272/10.7	9.6/12.1	480AB
265/70R17	115T	8J	804/31.7	272/10.7	9.6/12.1	480AB
31x10.50R15LT	109R	8½J	775/30.5	268/10.6	11.6/14.6	—

TC588

PCR



FLYING WING TYPE PATTERN DESIGN

- Strong visual sense of speed, drainage performance and curve control ability

FOUR LONGITUDINAL GROOVES

- Effective drainage and wet grip performance
- Better wet safety



CENTRAL WIDE RIB DESIGN

- Central wide rib design ensure the steering performance



WIDE PATTERN GROOVE DESIGN

- Avoid air flow vibration frequency effectively, reduce the abnormal wear and extend the life of the tyre



SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
255/45R17	98V	8½J	662/26.1	255/10.0	7.7/9.7	320AA
255/40ZR18	99/XLW	9J	661/26.0	260/10.2	7.7/9.7	320AA
235/45ZR18	98/XLW	8J	669/26.3	236/9.3	7.7/9.7	320AA
235/65R18	110HV	7J	763/30.0	250/9.8	7.7/9.7	320AA
265/30ZR19	93/XLW	9½J	643/25.3	271/10.7	7.7/9.7	320AA
245/35ZR19	93/XLW	8½J	655/25.8	248/9.8	7.7/9.7	320AA
275/40ZR19	—	—	—	—	7.7/9.7	320AA
245/45ZR19	102/XLW	8J	703/27.7	243/9.6	7.7/9.7	320AA
235/50R19	103V	7½J	719/28.3	255/10.0	7.7/9.7	420AA
235/55ZR19	105/XLW	7½J	741/29.2	245/9.6	7.7/9.7	320AA
245/55ZR19	103W	7½J	753/29.6	253/10.0	7.7/9.7	320AA
225/30R20	—	—	—	—	7.7/9.7	320AA
235/30ZR20	88/XLW	8½J	651/25.6	241/9.5	7.7/9.7	320AA

TC588 PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)	UTQG
245/35ZR20	95W	8½J	680/26.8	248/9.8	7.7/9.7	320AA
275/35ZR20	102/XLW	9½J	700/27.6	278/10.9	7.7/9.7	320AA
265/40ZR20	104/XLY	9½J	720/28.3	271/10.7	7.7/9.7	320AA
275/40ZR20	106/XLW	9½J	728/28.7	278/10.9	7.7/9.7	320AA
245/45ZR20	103W	8J	728/28.7	243/9.6	7.7/9.7	320AA
255/45ZR20	105/XLW	8½J	738/29.1	255/10.0	7.7/9.7	320AA
275/45ZR20	110W	9J	756/29.8	273/10.7	7.7/9.7	320AA
245/50ZR20	102W	7½J	754/29.7	253/10.0	7.7/9.7	320AA
255/50ZR20	109/XLY	8J	764/30.1	265/10.4	7.7/9.7	320AA
265/50ZR20	111/XLW	8½J	774/30.5	277/10.9	7.7/9.7	320AA
285/50ZR20	116/XLW	9J	794/31.3	297/11.7	7.7/9.7	320AA
275/55R20	117V	8½J	810/31.9	248/9.8	7.7/9.7	320AA
275/55ZR20	117W	8½J	810/31.9	248/9.8	7.7/9.7	320AA
275/60ZR20	115V	8J	838/33.0	279/11.0	7.7/9.7	320AA
295/25ZR22	97Y	10J	707/27.8	301/11.9	7.7/9.7	320AA
225/30ZR22	86/XLW	8J	695/27.4	230/9.1	7.7/9.7	320AA
235/30ZR22	90W	8½J	701/27.6	241/9.5	7.7/9.7	320AA
245/30ZR22	92W	8½J	707/27.8	248/9.8	7.7/9.7	320AA
255/30ZR22	95W	9J	713/28.1	260/10.2	7.7/9.7	320AA
265/30ZR22	97W	9½J	719/28.3	271/10.7	7.7/9.7	320AA
295/30ZR22	103W	10J	737/29.0	301/11.9	7.7/9.7	320AA
265/35ZR22	102W	9½J	745/29.3	271/10.7	7.7/9.7	320AA
285/35ZR22	106W	10J	759/29.9	290/11.4	7.7/9.7	320AA
265/40ZR22	106W	9½J	771/30.4	271/10.7	7.7/9.7	320AA
305/40ZR22	114W	11J	803/31.6	313/12.3	7.7/9.7	320AA
285/45ZR22	114/XLW	9½J	815/32.1	285/11.2	7.7/9.7	320AA
305/45ZR22	118W	10J	833/32.8	303/11.9	7.7/9.7	320AA
275/25ZR24	96/XLW	10J	748/29.4	283/11.1	7.7/9.7	320AA
255/30ZR24	97/XLW	9J	764/30.1	260/10.2	7.7/9.7	320AA
275/30ZR24	101W	9½J	776/30.6	278/10.9	7.7/9.7	320AA
295/35R24	110V	10½J	816/32.1	301/11.9	7.7/9.7	320AA
295/35ZR24	110W	10½J	816/32.1	301/11.9	7.7/9.7	320AA

TC595

PCR



'RAINY RIDER' DESIGN

- Effective drainage and wet grip performance
- Better wet safety



TC595 PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/Inch)	SECTION WIDTH (mm/Inch)	O.T.D (mm/32nds)
185R14C	102/100S	5½J	650 / 25.6	188 / 7.4	8.7 / 11.0
195R14C	106/104S	5½J	666 / 26.2	198 / 7.8	8.7 / 11.0
205R14C	109/107R	6	686 / 27.0	208 / 8.2	8.7 / 11.0
195R15C	106/104S	5½J	693 / 27.3	196 / 7.7	8.7 / 11.0
215/75R14C	112/110S	6	678 / 26.7	216 / 8.5	8.7 / 11.0
195/70R15C	104/102S	6J	655 / 25.8	201 / 7.9	8.7 / 11.0
205/70R15C	106/104S	6J	669 / 26.3	209 / 8.2	8.7 / 11.0
215/70R15C	109/107S	6½J	683 / 26.9	221 / 8.7	8.7 / 11.0
225/70R15C	112/110S	6½J	697 / 27.4	228 / 9.0	9.0 / 11.3
195/60R16C	99/97T	6J	640 / 25.2	201 / 7.9	8.7 / 11.0
215/60R16C	103/101TT	5½J	664 / 26.1	221 / 8.7	8.7 / 11.0
195/65R16C	104/102T	6J	660 / 26.0	201 / 7.9	8.7 / 11.0
205/65R16C	107/105T	6J	672 / 26.5	209 / 8.2	8.7 / 11.0
215/65R16C	109/107T	6½J	686 / 27.0	221 / 8.7	8.7 / 11.0
225/65R16C	112/110T	6½J	698 / 27.5	228 / 9.0	9.0 / 11.3
235/65R16C	115/113T	7J	712 / 28.0	240 / 9.4	9.0 / 11.3
175/75R16C	98/960	5J	558 / 22.0	177 / 7.0	8.7 / 11.0
185/75R16C	104/102S	5J	684 / 26.9	184 / 7.2	8.7 / 11.0
195/75R16C	107/105S	5½J	698 / 27.5	201 / 7.9	8.7 / 11.0
205/75R16C	110/118R	5½J	714 / 28.1	209 / 8.2	8.7 / 11.0
215/75R16C	116/114R	6J	728 / 28.7	216 / 8.5	8.7 / 11.0
225/75R16C	121/120R	6J	744 / 29.3	223 / 8.8	9.0 / 11.3

'HULK' DESIGN FOR SHOULDER

- Better stability
- Better load performance



'DE-NOISE' SHOULDER DESIGN

- Lower noise during running.
- Driving comfortably.



❄️ TC599

PCR



'3D SIPE' DESIGN

- Snow ejecting by sipe
- Better traction performance



'HULK' DESIGN FOR SHOULDER

- Better stability
- Better handling performance



'INLAID NAILS' DESIGN

- Increased friction with snow and ice surfaces
- Improved the safety of the tyre on the snow and ice pavement



TC599 PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)
185/65R15	88T	5½J	621 / 24.4	189 / 7.4
195/65R15	95/XLT	6J	635 / 25.0	201 / 7.9
205/55R16	94/XLT	6½J	632 / 24.9	214 / 8.4
225/65R17	106/XLT	6½J	724 / 28.5	228 / 9.0
265/70R17	115S	8J	804 / 31.7	272 / 10.7
LT225/75R16	115/112Q	6J	744 / 29.3	223 / 8.8
LT245/75R16	120/116Q	7J	774 / 30.5	248 / 9.8
LT245/70R17	119/116Q	7J	776 / 30.6	248 / 9.8
LT275/65R18	123/120Q	8J	815 / 32.1	279 / 11.0
LT275/70R18	125/122Q	8J	843 / 33.2	279 / 11.0

❄️ TC SNOWPAW

PCR



3D TWISTY SIPE PATTERN DESIGN

- With optimized angle, 3D twisty sipe pattern design ensures the rigidity of pattern block, at the same time, enhances the grip and effectively prevents slipping on ice and snow.

WIDE SHOULDER PATTERN DESIGN

- Wide shoulder pattern design enhances the handling and steering performance



HERRINGBONE PATTERN DESIGN

- Herringbone tread design and coherent circumferential pattern rib not only improve grip but also ensure lateral handling performance on ice and snow.



THREE LONGITUDINAL GROOVES

- Three longitudinal grooves, with excellent drainage performance, effectively prevent lateral slipping on ice and snow.



TC565 PASSENGER CAR TYRE

SIZE	LOAD INDEX/SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)
175/70R14	84T	5J	602 / 23.7	177 / 7.0	7.9 / 10.0
185/60R14	82T	5½J	578 / 22.8	189 / 7.4	7.9 / 10.0
195/60R14	86T	6J	590 / 23.2	201 / 7.9	8.1 / 10.2
185/60R15	84H	5½J	603 / 23.7	189 / 7.4	7.9 / 10.0
195/55R15	85T	6J	595 / 23.4	201 / 7.9	8.1 / 10.2
215/65R15	96H	6½J	661 / 26.0	221 / 8.7	8.1 / 10.2
215/70R15	98T	6½J	683 / 26.9	221 / 8.7	8.1 / 10.2
205/55R16	91H	6½J	632 / 24.9	214 / 8.4	8.1 / 10.2
215/60R16	95H	6½J	664 / 26.1	221 / 8.7	8.6 / 10.8
215/65R16	98H	6½J	686 / 27.0	221 / 8.7	8.1 / 10.2
215/50R17	95/XLV	7J	648 / 25.5	226 / 8.9	8.1 / 10.2
215/55R17	98/XLV	7J	668 / 26.3	226 / 8.9	8.1 / 10.2
215/60R17	96H	6½J	690 / 27.2	221 / 8.7	8.1 / 10.2
225/50R17	98/XLV	7J	658 / 25.9	233 / 9.2	8.1 / 10.2
225/55R17	101/XLV	7J	680 / 26.8	233 / 9.2	8.1 / 10.2
225/65R17	102H	6½J	724 / 28.5	228 / 9.0	8.1 / 10.2
255/45R17	102/XLH	8½J	662 / 26.1	255 / 10.0	8.1 / 10.2
265/65R17	112T	8J	776 / 30.6	272 / 10.7	8.6 / 10.8
215/55R18	99/XLH	7J	693 / 27.3	226 / 8.9	8.1 / 10.2
235/50R18	101/XLH	7½J	693 / 27.3	245 / 9.6	8.1 / 10.2
235/55R18	104/XLH	7½J	715 / 28.1	245 / 9.6	8.1 / 10.2
255/40R18	99V	9J	661 / 26.0	260 / 10.2	8.1 / 10.2
255/55R18	109/XLH	8J	737 / 29.0	265 / 10.4	8.1 / 10.2
235/50R19	103/XLV	7½J	719 / 28.3	245 / 9.6	8.1 / 10.2
245/45R19	102/XLV	8J	703 / 27.7	243 / 9.6	8.1 / 10.2
255/45R19	104/XLV	8½J	713 / 28.1	255 / 10.0	8.1 / 10.2
255/55R19	111/XLV	8J	763 / 30.0	265 / 10.4	8.1 / 10.2
235/55R20	105/XLV	7½J	766 / 30.2	245 / 9.6	8.1 / 10.2
245/45R20	103/XLV	8J	728 / 28.7	243 / 9.6	8.1 / 10.2
255/45R20	105/XLV	8½J	738 / 29.1	255 / 10.0	8.1 / 10.2
255/50R20	109/XLV	8J	764 / 30.1	265 / 10.4	8.1 / 10.2
255/55R20	110/XLV	8J	788 / 31.0	265 / 10.4	8.1 / 10.2
275/45R20	110/XLHt	9J	756 / 29.8	273 / 10.7	8.1 / 10.2

TC575

PCR



'3D SIPE' DESIGN

- Snow ejecting by sipe
- Better traction performance



UNIDIRECTIONAL PATTERN DESIGN

- Excellent self-cleaning ability
- Better grip performance



'SPIN-DRY' CAVERN DESIGN

- Good grip performance
- Avoiding sideslip



TC575 PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)
175/65R14	82T	5J	584 / 23.0	177 / 7.0	8.0 / 10.1
175/65R14	82H	5J	584 / 23.0	177 / 7.0	8.0 / 10.1
185/65R14	86T	5½J	596 / 23.5	189 / 7.4	8.0 / 10.1
185/65R14	86H	5½J	596 / 23.5	189 / 7.4	8.0 / 10.1
165/70R14	81T	5J	588 / 23.1	170 / 6.7	8.0 / 10.1
195/60R15	88T	6J	615 / 24.2	201 / 7.9	8.2 / 10.3
195/60R15	88H	6J	615 / 24.2	201 / 7.9	8.2 / 10.3
185/65R15	88T	5½J	621 / 24.4	189 / 7.4	8.0 / 10.1
185/65R15	88H	5½J	621 / 24.4	189 / 7.4	8.0 / 10.1
195/65R15	91T	6J	635 / 25.0	201 / 7.9	8.2 / 10.3
195/65R15	91H	6J	635 / 25.0	201 / 7.9	8.2 / 10.3
205/65R15	94T	6J	647 / 25.5	209 / 8.2	8.2 / 10.3
205/65R15	94H	6J	647 / 25.5	209 / 8.2	8.2 / 10.3
205/55R16	91H	6½J	632 / 24.9	214 / 8.4	8.2 / 10.3
215/55R16	97H	7J	642 / 25.3	226 / 8.9	8.2 / 10.3
215/55R16	97T	7J	642 / 25.3	226 / 8.9	8.2 / 10.3
205/60R16	96T	6J	652 / 25.7	209 / 8.2	8.2 / 10.3
205/60R16	96H	6J	652 / 25.7	209 / 8.2	8.2 / 10.3
215/60R16	99T	6½J	664 / 26.1	221 / 8.7	8.2 / 10.3
215/60R16	99H	6½J	664 / 26.1	221 / 8.7	8.2 / 10.3
235/55R17	99H	7½J	690 / 27.2	245 / 9.6	8.2 / 10.3
235/55R17	103H	7½J	690 / 27.2	245 / 9.6	8.2 / 10.3
235/55R17	103V	7½J	690 / 27.2	245 / 9.6	8.2 / 10.3
225/40R18	92H	8J	637 / 25.1	230 / 9.1	8.2 / 10.3
225/40R18	92V	8J	637 / 25.1	230 / 9.1	8.2 / 10.3

TC ICEHOLDER

PCR



'RAINY RIDER' DESIGN

- Effective drainage and wet grip performance
- Better wet safety



'3D SIPE' DESIGN

- Snow ejecting by sipe
- Better traction performance



'HULK' DESIGN FOR SHOULDER

- Better stability
- Better handling performance



TC ICEHOLDER PASSENGER CAR TYRE

SIZE	LOAD INDEX/ SPEED CODE	STANDARD RIM	OVERALL DIA (mm/inch)	SECTION WIDTH (mm/inch)	O.T.D (mm/32nds)
215/75R15	100S	6J	703 / 27.7	216 / 8.5	9.1 / 11.5
235/75R15	105S	6½J	733 / 28.9	235 / 9.3	9.1 / 11.5
215/70R16	100T	6½J	708 / 27.9	221 / 8.7	9.1 / 11.5
235/70R16	106T	7J	736 / 29.0	240 / 9.4	9.1 / 11.5
245/70R16	107T	7J	750 / 29.5	248 / 9.8	9.5 / 12.0
235/60R18	107H	7J	739 / 29.1	240 / 9.4	8.8 / 11.1
285/60R18	120T	8½J	799 / 31.5	292 / 11.5	8.8 / 11.1
255/60R19	113H	7½J	789 / 31.1	260 / 10.2	8.8 / 11.1
265/50R19	110H	8½J	749 / 29.5	277 / 10.9	8.8 / 11.1
275/55R19	111H	8½J	785 / 30.9	284 / 11.2	8.8 / 11.1
275/50R20	113H	8½J	784 / 30.9	284 / 11.2	8.8 / 11.1